

Proudly supplied by



**RovicLeers**

**CAPE TOWN +27 (0)21 907 1700**  
**admin@rovicleers.co.za**

**JOHANNESBURG +27 (0)11 396 6200**  
**infojhb@rovicleers.co.za**

**PIETERMARITZBURG +27(0) 33 346 2727**  
**infopmb@rovicleers.co.za**

## ROME - Offset Disc Harrows

### TAW Series - Offset Disc Harrow (Rome)

#### General Specifications

- Ø 711mm x 10mm thick Concave notched Disc
- Disc Spacing 305mm
- Greasable dual tapered roller bearings
- Mechanical adjustable working depth
- Adjustable Disc blade scrapers
- Heavy duty wear plates
- Tyres (16 ,20 & 24 Disc) 12.5L x 15
- Tyres (28 & 32 Disc) 21.5L x 16.1
- Drawbar Jack stand and safety chain
- Requires one hydraulic outlet



Stock Code	Model	No of Disc	Working depth	kW Required	Wt. per disc	Net weight
UTAW-16	TAW -16	16	229mm	53 - 67kW	172kg	2,757kg
UTAW-20S	TAW -20S	20	229mm	62 - 76kW	160kg	3,201kg
UTAW-24	TAW -24	24	229mm	75 - 88kW	157kg	3,778kg
UTAW-28	TAW -28	28	229mm	99 - 113kW	174kg	4,885kg
UTAW-32	TAW -32	32	229mm	109 - 123kW	167kg	5,368kg

#### Optional Equipment

	Cylinder Rod stops (16 to 28 Disc)
	Cylinder Rod stops (32 Disc)